



## DESCRIPTIVE

- ➔ Kohler Co. Provides one-source responsibility for the generating system and accessories.
- ➔ The generator set and its components are prototyped, factory-built, and production-tested.
- ➔ A one-year limited warranty covers all systems and components
- ➔ Electronic governor
- ➔ Mechanically welded chassis with antivibration suspension
- ➔ Radiator for core temperature of 48/50°C max with mechanical fan
- ➔ Protective grille for fan and rotating parts (CE option)
- ➔ Exhaust compensators with flanges
- ➔ 24 V charge alternator and starter
- ➔ Delivered with oil and coolant -30°C
- ➔ Manual for use and installation

## POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1. ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.  
DCC : Data Center Continuous Power ratings apply to Data Center installations where a reliable utility power is available and comply with Uptime institute Tier III and IV requirements. At constant or varying load, the number of generator set operating hours is unlimited. A 10% overload capacity is available for one hour in twelve. Average load factor : ≤ 100%.

## TERMS OF USE

According to the standard, the nominal power assigned by the genset is given for 25°C Air Inlet Temperature, of a barometric pressure of 100 kPA (100 m A.S.L), and 30 % relative humidity. For particular conditions in your installation, refer to the derating table.

## ASSOCIATED UNCERTAINTY

For the generator sets used indoor, where the acoustic pressure levels depend on the installation conditions, it is not possible to specify the ambient noise level in the operating and maintenance instructions. You will also find in our operating and maintenance instructions a warning concerning the air noise dangers and the need to implement appropriate preventive measures.

# KM1650C

Engine type	S12R-F1PTAW2
Alternator type	LSA 50.2 L8
Performance class	G3

## GENERAL CHARACTERISTICS

Frequency (Hz)	50
Voltage (V)	400/230
Standard control panel	Basic terminal block
Optional control panel	M80
Optional control panel	DEC4000
Optional control panel	APM802

## POWER

Voltage	ESP		PRP		DCC (*)		Standby Amps
	kWe	kVA	kWe	kVA	kWe	kVA	
415/240	1320	1650	1200	1500	1200	1500	2296
400/230	1320	1650	1200	1500	1200	1500	2382
380/220	1320	1650	1200	1500	1200	1500	2507

## DIMENSIONS COMPACT VERSION

Length (mm)	5090
Width (mm)	2200
Height (mm)	2510
Dry weight (kg)	12043
Tank capacity (L)	0

## DIMENSIONS SOUNDPROOFED VERSION

Commercial reference of the enclosure	N/A
Length (mm)	0
Width (mm)	0
Height (mm)	0
Dry weight (kg)	0
Tank capacity (L)	0
Acoustic pressure level @1m in dB(A)	0
Sound power level guaranteed (Lwa)	0
Acoustic pressure level @7m in dB(A)	0

## KM1650C

### ENGINE CHARACTERISTICS

#### GENERAL ENGINE DATA

Engine model	MITSUBISHI
Engine type	S12R-F1PTAW2
Air inlet	Turbo
Cylinders arrangement	V
Number of cylinders	12
Displacement (L)	49.03
Charge Air coolant	Air/Water DC
Bore (mm) x Stroke (mm)	170 x 180
Compression ratio	14.5 : 1
Speed (RPM)	1500
Pistons speed (m/s)	9
Maximum stand-by power at rated RPM (kW)	1462
Frequency regulation, steady state (%) +/- 0.5%	
BMEP (bar)	21.69
Governor type	Electronic

#### COOLING SYSTEM

Radiator & Engine capacity (L)	498.00
Max water temperature (°C)	98
Outlet water temperature (°C)	95
Fan power (kW)	34
Fan air flow w/o restriction (m3/s)	25.3
Available restriction on air flow (mm H2O)	20
Type of coolant	Glycol-Ethylene
Thermostat modulating range HT (°C)	71-85

#### EMISSIONS

Emission PM (mg/Nm3)	50
Emission CO (mg/Nm3)	650
Emission HCNOx (g/kWh)	N/A
Emission HC (mg/Nm3)	150

#### EXHAUST

Exhaust gas temperature @ ESP 50Hz (°C)	550
Exhaust gas flow @ ESP 50Hz (L/s)	5766
Max. exhaust back pressure (mm H2O)	600

#### FUEL

Consumption @ 110% load (L/h)	360
Consumption @ 100% load (L/h)	320
Consumption @ 75% load (L/h)	240
Consumption @ 50% load (L/h)	170
Maximum fuel pump flow (L/h)	N/A

#### OIL

Oil capacity (L)	180
Min. oil pressure (bar)	4.9
Max. oil pressure (bar)	6.4
Oil consumption 100% load (L/h)	N/A
Oil sump capacity (L)	150

#### HEAT BALANCE

Heat rejection to exhaust (kW)	1321
Radiated heat to ambient (kW)	114
Heat rejection to coolant (kW)	496

#### AIR INTAKE

Max. intake restriction (mm H2O)	400
Intake air flow (L/s)	2183



## CONTAINER CPU40 Ssi

Commercial reference of the enclosure

Length (mm)	12192
Width (mm)	2438
Height (mm)	2896
Dry weight (kg)	23460
Tank capacity (L)	500
Acoustic pressure level @1m in dB(A)	79
Sound power level guaranteed (Lwa)	102
Acoustic pressure level @7m in dB(A)	71

,U '88 < ' U\_8+\_ &Z

M80, transfer of information



The control unit can be used as a basic terminal block for connecting a control box,

Offers the following functions:

Emergency stop button, customer connection terminal block, CE.

The M80 is a dual-function control unit. It can be used as a basic terminal block for connecting a control box and as an instrument panel with a direct read facility, with displays giving a global view of your generating set's basic parameters.

Offers the following functions:

Engine parameters: tachometer, working hours counter, coolant temperature indicator, oil pressure indicator, emergency stop button, customer connection terminal block, CE.

## APM802 dedicated to power plant management



The new APM802 command/control system is specifically designed for operating and monitoring power plants for markets including hospitals, data centres, banks, the oil and gas sector, industries, IPP, rental and mining. This unit is available as standard on all generating sets from 275 Kva designed for coupling. It is optional on the rest of our range.

The Human Machine Interface, designed in collaboration with a company specialising in interface design, facilitates operations with a large 100% touch screen. The pre-configured system for power plant applications features a brand new customisation function which complies with the international standard IEC 61131-3. New communication functions (PLC and regulation), improve the high level of equipment availability in the installation.

### Advantages:

- Dedicated to power plant management.
- Specially researched ergonomics.
- High level of equipment availability.
- Modularity and long service life guaranteed.
- Making it easy to extend the installation

For more information, please refer to the sales documentation.